

EVA 1540

Physical	Nominal Value	Unit	Test Method
Density		g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)		g/10 min	ASTM D1238
Vinyl Acetate Content		wt%	Internal Method
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)		psi	ASTM D638
Tensile Elongation (Break)		%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature		°F	ASTM D1525
Melting Temperature		°F	
Features			
Features may also be described by the following terms: Good Processability, Easy Processing, Good Adhesion.			
Available Documents			
Technical Datasheet (English)			

Product Description: HANWHA EVA 1540 is manufactured by Dow autoclave high pressure process and designed for variety hot melt adhesive application. EVA 1540 is well known for its excellent adhesive property, mixing property with other raw materials and high quality assurance.

General

Material Status : Commercial: Active

Availability : Asia Pacific , Europe , North America

Additive : Antioxidan

Features : Antioxidant , Good Adhesion , Good Processability

Uses : Adhesives

Forms : Pellets

Producer: HANWHA.Korea